

StreetScooter		WORK		WORK		WORK L	
Engine / Electric	Engine type: Electric engine		Permanent synchronous motor	Permanent synchronous motor	Permanent synchronous motor		Permanent synchronous motor
	Peak power / 30 minutes of continuous power output	kW (HP)	48 (65) / 39 (53)	48 (65) / 39 (53)	48 (65) / 39 (53)		48 (65) / 39 (53)
	Maximum torque	Nm	200	200	200		200
	Drive		Front-wheel drive	Front-wheel drive	Front-wheel drive		Front-wheel drive
Battery/ charging system	Battery		Lithium-ion battery	Lithium-ion battery	Lithium-ion battery		Lithium-ion battery
	Battery capacity	kWh	20	40	40		40
	AC charging system connector	kW	Type 2 (12 A, 230V)	Type 2 (12 A, 230V)	Type 2 (12 A, 230V)		Type 2 (12 A, 230V)
Performance	Range (according to NEDC) ¹	km	101	205	205		187
	CO2 emissions (measured in line with EU norms)	g/km	0	0	0		0
	Efficiency rating		A+	A+	A+		A+
	Top speed	km/h	85	85	85		85
Chassis / control	Front axle		Independent suspension, Macpherson struts	Independent suspension, Macpherson struts	Independent suspension, Macpherson struts		Independent suspension, Macpherson struts
	Rear axle		Torsion bar spring axle	Torsion bar spring axle	Torsion bar spring axle		Torsion bar spring axle
	Rim size front axle / front axle		6J x 15 H2 ET 38 / 6J x 15 H2 ET 38	6J x 15 H2 ET 38	6J x 15 H2 ET 38		6J x 15 H2 ET 38 / 6J x 15 H2 ET 68
	Tire size front axle / rear axle		195/65 R15 91L / 195/65 R15 91L	195/65 R15 91L	195/65 R15 91L		195/65 R15 91L / 195/70 R15 C 104/- R
	Brake system		Hydraulic brakes with power brake system	Hydraulic brakes with power brake system	Hydraulic brakes with power brake system		Hydraulic brakes with power brake system
	Front		Disc brakes	Disc brakes	Disc brakes		Disc brakes
	Rear		Drum brakes	Drum brakes	Drum brakes		Drum brakes
	Axle track	mm	1,454 / 1,648	1,454 / 1,649	1,454 / 1,649		1,454 / 1,573
	Turning circle	m	10,72	10,72	10,72		13,28
Dimensions BOX ²⁾	Length / width / height	mm	4,709 / 2,087 / 2,039	4,709 / 2,087 / 2,039	4,709 / 2,087 / 2,039		5,784 / 2,087 / 2,347
	Total width excluding exterior mirrors	mm	1,925	1,925	1,925		1,925
	Loading edge	mm	772	772	772		845
	Box cargo space length / width / height	mm	2,050 / 1,665 - 1,745 / 1,195	2,050 / 1,665 - 1,745 / 1,195	2,050 / 1,665 - 1,745 / 1,195		3,150 / 1,675 - 1,731 / 1,407
	Rear door loading width / height / weight	mm	1,265 / 1,135	1,265 / 1,135	1,265 / 1,135		1,390 / 1,335
	Sliding door loading width / height	mm	881 / 1,135	881 / 1,135	881 / 1,135		1,265 / 1,335
Weight BOX ³⁾	Total vehicle load capacity	m ³	4,3	4,3	4,3		8
	Gross vehicle weight	kg	2,180	2,180	2,180		2,600
	Curb weight	kg	1,460	1,595	1,595		1,695
	Payload	kg	720	585	585		905
	Permissible axle load front / rear		950 / 1,230	950 / 1,230	950 / 1,230		1,100 / 1,600
Dimensions Pickup ²⁾	Length / width / height	mm	4,741 / 2,087 / 1,859	4,741 / 2,087 / 1,859	4,741 / 2,087 / 1,859		5,840 / 2,087 / 1,859
	Total width excluding exterior mirrors	mm	1,814	1,814	1,814		1,814
	Loading edge	mm	910	910	910		910
	Pickup cargo bed length, interior	mm	2,087	2,087	2,087		3,177
	Pickup cargo bed width, interior	mm	1,759	1,759	1,759		1,757
	Pickup cargo bed height, interior	mm	400	400	400		400
Weight Pickup	Gross vehicle weight	kg	2,180	2,180	2,180		2,600
	Curb weight	kg	1,460	1,595	1,595		1,710
	Payload	kg	720	585	585		890
	Lashing rings, number		6	6	6		8
	Lashing rings, lashing capacity ³⁾	daN	650	650	650		650
Dimensions and weights Pickup ²⁾	Length / width / height	mm	4,676 / 2,087 / 1,861	4,676 / 2,087 / 1,861	4,676 / 2,087 / 1,861		5,784 / 2,087 / 1,8867
	Total width excluding exterior mirrors	mm	1,796	1,796	1,796		1,796
	Loading edge	mm	-	-	-		-
	Gross vehicle weight	kg	2,180	2,180	2,180		2,600
	Curb weight	kg	1,280	1,415	1,415		1,465
	Payload	kg	900	765	765		1,135

¹⁾ Range according to NEDC. The actual range depends on different factors such as personal driving style, speed, topography, payload, outside temperature and electrical load. These factors should be taken into consideration whenever possible by drivers for maximum vehicle range.

²⁾ Information on dimensions and weights may differ owing to equipment. All weights refer to the vehicle in running order and include driver (75 kg) and liquids.

³⁾ In accordance with DIN75410-1