

	StreetScooter		WORK 20kWh - 40kWh	WORK L
Engine / Electric / Battery	Engine type: Electric engine		Permanent synchronous motor	Permanent synchronous motor
	Peak power / 30 minutes of continuous power output	kW [HP]	48 [65] / 39 [53]	48 [65] / 39 [53]
	Maximum torque	Nm	200	200
	Drive		Front-wheel drive	Front-wheel drive
	Battery		Lithium-ion battery	Lithium-ion battery
	Battery capacity	kWh	20 - 40	40
	AC charging system connector		Type 2 [12 A, 230V]	Type 2 [12 A, 230V]
Performance	Range (according to NEDC) ¹	km	101 - 205	187
	CO2 emissions (measured in line with EU norms)	g/km	0	0
	Efficiency rating		A+	A+
	Top speed	km/h	85	85
	Turning circle	m	10,72	13,28
Dimensions & Weight BOX ²⁾	Length / width / height	mm	4,709 / 2,087 / 2,039	5,784 / 2,087 / 2,347
	Total width excluding exterior mirrors	mm	1,925	1,925
	Loading edge	mm	772	845
	Box cargo space length / width / height	mm	2,050 / 1,665 - 1,745 / 1,195	3,150 / 1,675 - 1,731 / 1,407
	Rear door loading width / height / weight	mm	1,265 / 1,135	1,390 / 1,335
	Sliding door loading width / height	mm	881 / 1,135	1,265 / 1,335
	Total vehicle load capacity	m ³	4,3	8
	Gross vehicle weight	kg	2,180	2,600
	Curb weight	kg	1,460 - 1,595	1,695
	Payload	kg	720 - 585	905
Permissible axle load front / rear		950 / 1,230	1,100 / 1,600	
Dimensions & Weight Pickup ²⁾	Length / width / height	mm	4,741 / 2,087 / 1,859	5,840 / 2,087 / 1,859
	Total width excluding exterior mirrors	mm	1,814	1,814
	Loading edge	mm	910	910
	Pickup cargo bed length, interior	mm	2,087	3,177
	Pickup cargo bed width, interior	mm	1,759	1,757
	Pickup cargo bed height, interior	mm	400	400
	Gross vehicle weight	kg	2,180	2,600
	Curb weight	kg	1,460 - 1,595	1,710
	Payload	kg	720 - 585	0,89
	Lashing rings, number		6	8
Lashing rings, lashing capacity ³⁾	daN	650	650	
Dimensions and Weight Pickup ²⁾	Length / width / height	mm	4,676 / 2,087 / 1,861	5,784 / 2,087 / 1,8867
	Total width excluding exterior mirrors	mm	1,796	1,796
	Loading edge	mm	-	-
	Gross vehicle weight	kg	2,180	2,600
	Curb weight	kg	1,280 - 1,415	1,465
	Payload	kg	900 - 765	1,135

¹⁾ Range according to NEDC. The actual range depends on different factors such as personal driving style, speed, topography, payload, outside temperature and electrical load. These factors should be taken into consideration whenever possible by drivers for maximum vehicle range.

²⁾ Information on dimensions and weights may differ owing to equipment. All weights refer to the vehicle in running order and include driver (75 kg) and liquids.

³⁾ In accordance with DIN75410-1